

English Translation
for
EP 59050939

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 60-195957

(43)Date of publication of application : 04.10.1985

(51)Int.Cl.

H01L 23/48

H01L 23/28

(21)Application number : 59-050939

(71)Applicant : HITACHI LTD

(22)Date of filing : 19.03.1984



(72)Inventor : TANIGAWA TAKAHIRO
NAKAZAWA HIROSHI

(54) LEAD FRAME

(57)Abstract:

PURPOSE: To improve the contacting property between a lead frame and a resin and to enhance the sealability and the reliability by stepwisely forming the side of the lead frame, and increasing the contacting surface with the resin.

CONSTITUTION: Projections 8, 15 are formed on tabs 4, 13 of a lead frame, tab hanging lead 5 and the sides of leads 6, 14. The projection 8 is formed by a suitable method. The lead frame 12 is, for example, composed of 42-alloy. A semiconductor chip 9 is formed, for example, of silicon single crystal substrate, many circuit elements are formed in the chip by the know technique, and one circuit function is formed. A resin sealer 11 is formed, for example, of epoxy resin, and molded by a known transfer molding method.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office